

Product Specification


Outdoor P2.5

Parameter of Outdoor P2.5 Series

	Parameter Name	Product Parameter
Module	LED Type	SMD1516
	Pixel Pitch	2.5mm
	Module Resolution (W×H)	128X64=8192 Pixels
	HUB	HUB75
	Module Dimension	320mm×160mm×17.5mm
	Module Weight	0.46±0.02kg
Optical	Single-dot Brightness Calibration	Support
	White Balance Brightness	≥4000 CD/m ²
	Standard Color Temperature	6500K (1000K ~ 9500K Adjustable)
	Beam Angle (Hor/Ver°)	140°/Looking up 70°、Looking down 40°
	Contrast Ratio	3000 : 1
Electronic	Input Power <Max>	879W/m ²
	Input Power <Typical>	293W/m ²
	Power Voltage	AC90 ~ 132V/ AC186 ~ 264V, Frequency 47~63 (Hz)
Performance	Frame Changing Frequency	≥60Hz
	Drive Mode	Constant Current Drive / 16 Scan
	Refresh Rate	≥1920Hz / ≥3840Hz
	Processing Depth	12~14 Bit
	Video Support	2K HD, 4K UHD
Environment	Life Typical Value (HRS)	50000H
	Working Temperature/ Humidity Range (°C/RH)	-20°C~50°C / 10%~65%RH (No Condensation)
	Storage Temperature / Humidity Range (°C/RH)	-10°C~30°C / 10%~60%RH (No Condensation)

Remark: 1. The above parameters are typical or recommended
 2. Product parameters or configuration adjustments without notice
 3. Customized products, please confirm the parameters with our company

Product Picture of Outdoor P2.5 Series



Hole Position of Outdoor P2.5 Series

